

ARMOUR PREMIUM CARPET FILM



WATERPROOF



CLEAN
REMOVAL



CUSTOM
BRAND IT

Armour Premium Carpet Film provides reliable temporary protection for carpeted areas during construction and renovation projects, delivering clean removal and lasting defense against common jobsite messes.

- Made from tear-resistant film for durability and dependable coverage
- Shields carpets from dirt, dust, paint, debris, and other construction damage
- Fully waterproof and protects for up to 45 days with easy, clean removal
- White film makes it easy to identify uncovered areas and can also be used for construction markings
- Commonly used to protect hallways, rooms, stairs, and other carpeted areas from minor construction damage like scuffs, scratches, or dust in low-traffic or short-term projects

ITEM CODE	SIZE	WEIGHT	PACKAGED
APCF24200	24in X 200ft (400 sq.ft.)	5.8lb	72 / skid
APCF24500	24in X 500ft (1000 sq.ft.)	13lb	42 / skid
APCF36200	36in X 200ft (600 sq.ft.)	9lb	72 / skid
APCF36500	36in X 500ft (1500 sq.ft.)	19.5lb	42 / skid
APCF48200	48in X 200ft (800 sq.ft.)	11.5lb	72 / skid
APCF48500	48in X 500ft (2000 sq.ft.)	26lb	42 / skid

ARMOUR PREMIUM CARPET FILM

<u>Physical Properties</u>	<u>Details</u>
Product Material	Polyethylene (PE) Film
Adhesive Type	Water Based Acrylic Solvent
Product Colour	White
Logo Colour	Blue
Shelf Life	12 months
Clean Removal* / UV Rating	1.5 months
Packaging Size	1 roll per carton
HS Code	3919.90.00.20

<u>Specification Properties</u>	<u>Metric</u>	<u>Standard/Imperial</u>
Application Temperature Range	-15 35°C ±10%	5 95°F ±10%
Operating Temperature Range	-10 35°C ±10%	14 95°F ±10%
Product Thickness	0.071 mm	2.8 mil
Adhesive Thickness	0.007 mm	0.27 mil
TOTAL Product Thickness	0.078 mm	3.07 mil
Product Width	Varies	Varies
Product Height/Length	Varies	Varies
Tensile Strength	2.657 kgf/25mm	5.85 lbs/in
Adhesion Strength	0.6 kgf/25mm	1.32 lbs/in
Unwinding Force	0.05 kgf/25mm	0.11 lbs/in
Elongation at Break		>300 %

*Certain additives in the product adhesive and/or material finishes of the surface it is applied to may soften the products adhesive over time, potentially leaving adhesive residue. There is no guarantee that adhesive products will not remove existing finishes when removed, due to the quality of bond on existing paint, wax, or other coatings that the adhesive product is applied to. Given the diversity of factors that can affect the use and performance of any Product, you, as the user, are solely responsible for evaluating the Product and determining whether it is fit for the intended purpose and suitable for your method of application.