

ARMOUR PREMIUM HARD SURFACE FILM



WATERPROOF



CLEAN
REMOVAL



CUSTOM
BRAND IT

Armour Premium Hard Surface Film is a dependable temporary protection solution designed to keep finished surfaces safe during construction and renovation projects, offering clean removal and reliable performance for short-term applications.

- Made from durable tear-resistant film for long-lasting coverage
- Protects hard surfaces from scuffs, scratches, dust, paint, drywall mud, and more
- Fully waterproof and provides up to 45 days of protection with easy, clean removal
- Blue film ensures visibility for quick identification of covered and uncovered areas
- Commonly used to protect hard floors, cabinets, lockers, and other hard surfaces from minor construction damage like scuffs, scratches, or dust in low-traffic or short-term projects

ITEM CODE	SIZE	WEIGHT	PACKAGED
APHSF24500	24in X 500ft (1000 sq.ft)	13lb	42 / skid
APHSF36500	36in X 500ft (1500 sq.ft.)	19.5lb	42 / skid
APHSF48500	48in X 500ft (2000 sq.ft.)	26lb	42 / skid

ARMOUR PREMIUM HARD SURFACE FILM

<u>Physical Properties</u>	<u>Details</u>
Product Material	Polyethylene (PE) Film
Adhesive Type	Water Based Acrylic Solvent
Product Colour	Blue
Logo Colour	White
Shelf Life	12 months
Clean Removal* / UV Rating	1.5 months
Packaging Size	1 roll per carton
HS Code	3919.90.00.20

<u>Specification Properties</u>	<u>Metric</u>	<u>Standard/Imperial</u>
Application Temperature Range	-15 35°C ±10%	5 95°F ±10%
Operating Temperature Range	-10 35°C ±10%	14 95°F ±10%
Product Thickness	0.071 mm	2.8 mil
Adhesive Thickness	0.007 mm	0.27 mil
TOTAL Product Thickness	0.078 mm	3.07 mil
Product Width	Varies	Varies
Product Height/Length	Varies	Varies
Tensile Strength	2.657 kgf/25mm	5.85 lbs/in
Adhesion Strength	0.6 kgf/25mm	1.32 lbs/in
Unwinding Force	0.05 kgf/25mm	0.11 lbs/in
Elongation at Break		> 300 %

*Certain additives in the product adhesive and/or material finishes of the surface it is applied to may soften the products adhesive over time, potentially leaving adhesive residue. There is no guarantee that adhesive products will not remove existing finishes when removed, due to the quality of bond on existing paint, wax, or other coatings that the adhesive product is applied to. Given the diversity of factors that can affect the use and performance of any Product, you, as the user, are solely responsible for evaluating the Product and determining whether it is fit for the intended purpose and suitable for your method of application.