

# ARMOUR NEOPRENE FLOOR RUNNER



RE-USABLE



WATERPROOF



FLAT + FAST  
INSTALL



SLIP RESISTANT



CUSTOM  
BRAND IT

Armour Neoprene Floor Runner is a reliable and reusable temporary walkway solution that delivers durable surface protection while ensuring safety and ease of use on a variety of jobsites.

- Made from tough neoprene for long-lasting performance
- Anti-slip underside keeps runners securely in place without adhesives, ideal for stairs and smooth surfaces
- Lays flat for immediate use, then easily rolls up for convenient storage and reuse
- Designed to act as temporary walkways for safe, efficient traffic flow
- Commonly used to protect surfaces serving as access routes from moderate to major construction damage like repeated impacts, heavy wear, or sustained activity in busy or long-term projects

| ITEM CODE | SIZE                   | WEIGHT | PACKAGED |
|-----------|------------------------|--------|----------|
| AFR2720G  | 27in X 20ft(45 sq.ft.) | 10.6lb | 1 / box  |

## ARMOUR NEOPRENE FLOOR RUNNER

| <u>Physical Properties</u> | <u>Details</u>         |
|----------------------------|------------------------|
| Product Material           | Foam Natural Rubber    |
| Product Coating            | Polyester (PES) Fabric |
| Product Colour             | Grey/Black             |
| Packaging Size             | 1 roll per carton      |
| HS Code                    | 4016.91.00.90          |

| <u>Specification Properties</u>  | <u>Metric</u> | <u>Standard/Imperial</u> |
|----------------------------------|---------------|--------------------------|
| Product Thickness                | 1.59 mm       | 62.5 mil                 |
| TOTAL Product Thickness          | 1.59 mm       | 62.5 mil                 |
| Product Weight / Density         | 950 g/sq.m    | 0.195 lbs/sq.ft.         |
| Product Coating Weight / Density | 200 g/sq.m    | 0.04 lbs/sq.ft.          |
| TOTAL Product Weight / Density   | 1150 g/sq.m   | 0.235 lbs/sq.ft.         |
| Product Width                    | 686 mm        | 27 in                    |
| Product Height/Length            | 6.1 m         | 20 ft                    |
| Tensile Strength                 | 255 kgf/25mm  | 3626 lbs/in              |
| Elongation at Break              |               | 1 %                      |
| Puncture Resistance              |               | 10%                      |
| Water Absorption                 |               | 10%                      |
| Oil Absorption                   |               | 8%                       |