

# ARMOUR SECURE-SEAM TAPE



WATERPROOF



CUSTOM  
BRAND IT

Armour Secure-Seam Tape is a cost-effective seaming solution designed to hold temporary surface protection materials securely in place, ensuring a fully sealed off solution on jobsites.

- Constructed with durable adhesive backing for strong hold on protection materials
- Designed for seaming surface protection products to themselves, not to finished surfaces – for a tape solution that offers clean removal, try Armour Tape or Armour Pro-Clean Tape
- Provides dependable adhesion that prevents shifting, keeping protection secure throughout the project
- Cost-effective solution that delivers reliable performance for a range of jobsite needs
- Commonly used for seaming protection materials to each other on minor to major construction projects

| ITEM CODE | SIZE        | WEIGHT | PACKAGED  |
|-----------|-------------|--------|-----------|
| ASST2216  | 2in X 216ft | 0.4lb  | 72 / case |

# ARMOUR SECURE-SEAM TAPE

| <u>Physical Properties</u> | <u>Details</u>                       |
|----------------------------|--------------------------------------|
| Product Material           | Low Density Polyethylene (LDPE) Film |
| Adhesive Type              | UV Stabilized Synthetic Rubber       |
| Product Colour             | Black                                |
| Logo Colour                | White                                |
| Shelf Life                 | 12 months                            |
| Packaging Size             | 72 rolls per case                    |

| <u>Specification Properties</u> | <u>Metric</u> | <u>Standard/Imperial</u> |
|---------------------------------|---------------|--------------------------|
| Application Temperature Range   | 12 to 43°C    | 54 to 110°F              |
| Operating Temperature Range     | -2 to 60°C    | 30 to 140°F              |
| Product Thickness               | 0.062 mm      | 2.44 mil                 |
| TOTAL Product Thickness         | 0.062 mm      | 2.44 mil                 |
| Product Width                   | 5.08 cm       | 2in                      |
| Product Height/Length           | 65.84 m       | 216ft                    |
| Tensile Strength                | 630 N/100 mm  | 36lbs/in                 |
| Adhesion Strength               | 61 N/100 mm   | 57oz/in                  |
| Elongation at Break             |               | 200 %                    |

\*Certain additives in the product adhesive and/or material finishes of the surface it is applied to may soften the products adhesive over time, potentially leaving adhesive residue. There is no guarantee that adhesive products will not remove existing finishes when removed, due to the quality of bond on existing paint, wax, or other coatings that the adhesive product is applied to. Given the diversity of factors that can affect the use and performance of any Product, you, as the user, are solely responsible for evaluating the Product and determining whether it is fit for the intended purpose and suitable for your method of application.