

ARMOUR PROTECTION FLEECE



RE-USABLE



WATERPROOF



FLAT + FAST
INSTALL



BREATHABLE



CUSTOM
BRAND IT

Armour Protection Fleece provides advanced temporary surface protection designed for curing floors and high-shine finishes, combining breathability, waterproofing, and durability for demanding jobsite conditions.

- Made from soft non-woven fibres with a tacky anti-slip underside and waterproof top layer
- Stays securely in place without sliding and prevents liquid penetration for reliable protection
- Armour Breathe Technology allows vapor permeability of 70 g/m² per 24 hours, enabling fresh floors to cure while remaining protected
- Soft, non-abrasive surface guards against scuffs and scratches on smooth, high-shine finishes
- Commonly used to protect hard floors such as concrete, hardwood, vinyl, tile, laminate and more, from moderate to major construction damage like repeated wear, or sustained activity in busy or long-term projects

ITEM CODE	SIZE	WEIGHT PACKAGED	
APF36100	36in X 100ft (300 sq.ft.)	10.3lb	30 / skid
APF150	1m X 50m (538 sq.ft.)	18.5lb	30 / skid

ARMOUR PROTECTION FLEECE

<u>Physical Properties</u>	<u>Details</u>
Product Material	100% Polyester (PES) Non-woven Fiber, with Breathable PE-film
Adhesive Type	Water Based Acrylic
Product Color	White
Logo Color	Black
Shelf Life	12 months
Clean Removal* / UV Rating	3 months
Packaging Size	1 roll per carton
HS Code	5603.94.00.90

<u>Specification Properties</u>	<u>Metric</u>	<u>Standard/Imperial</u>
Operating Temperature Range	-10 40°C ±10%	50 104°F ±10%
Product Thickness	2.5 mm	98 mil
TOTAL Product Thickness	2.5 mm	98 mil
Product Weight / Density	120 g/sq.m	0.024 lbs/sq.ft.
Film Weight / Density	40 g/sq.m	0.008 lbs/sq.ft.
TOTAL Product Weight / Density	160 g/sq.m	0.032 lbs/sq.ft.
Product Width	Varies	Varies
Product Height/Length	Varies	Varies
Vapor Permeability	70 gr/m2/24hr	0.014 lbs/sq.ft.

*Certain additives in the product adhesive and/or material finishes of the surface it is applied to may soften the products adhesive over time, potentially leaving adhesive residue. There is no guarantee that adhesive products will not remove existing finishes when removed, due to the quality of bond on existing paint, wax, or other coatings that the adhesive product is applied to. Given the diversity of factors that can affect the use and performance of any Product, you, as the user, are solely responsible for evaluating the Product and determining whether it is fit for the intended purpose and suitable for your method of application.